

Version No.: 0 Update Date: 27.08.23

## PRODUCT DATA SHEET

## **WEATHERBOND PLUS**

Description	A high-performance water-based paint that possesses superior exterior durability with good water proofing and long lasting colour.			
Туре	Pure Acrylic Emulsion with Micro Gel Technology			
Uses	Premium grade emulsion with excellent protective and decorative functions for all ex masonry surfaces such as:			
	- Cement plasters	- Concrete	- Brickworks	
Finish	Sheen			
	Colour: Wide range of decorative colours as per colour card. Special colours on request.			
Features	- Excellent weathering resistance			
	- 12 years colour performance			
	- Good washability and water proofing			
	- Excellent to Alkaline & Efflorescence properties			
	- Good dirt pick up resistance			
	- Excellent resistance to fungus and algae growth			
	- Good adhesion on stable substrates			
	- Easy apply with good flow & leveling properties			
	- APEO free, Non-toxic, does not contain Lead, Mercury and heavy metals			
	- Low VOCs (containing < 30g/L VOC, meeting the VOC requirement)			
	- Green Label Certificate			
APPLICATION DATA	`			
Surface Preparation	Surface must be clean, dry, and stable.			
	Suggested Treatment:			
	<u>Dirt/Powder:</u> High pressure water wash. Mild detergent may be used. For very powdery surface, apply a coat of NIPPON ACRYLIC 5170 WALL SEALER after cleaning.			
	Old Paint/Plaster/Skimcoat: Unstable old film / substrate should be removed by chisel,			
	scraper, and power grinder whichever is appropriate. Uneven substrates must be replastered with an approved putty / skimcoat.			
	Moisture: High moisture will cause paint defect. Observe the following level prior to painting:			
	- Masonry: below 16% by Protimeter Mini BLD 2000 Moisture meter			
	below 60% by Lutron MS-7003 Moisture meter			
	All water seepage must be checked and repaired.			

Under license from NIPPON PAINT (SINGAPORE) Co., Pte Ltd. No.

1, First Lok Yang Road, Jurong, Singapore 629728, Singapore



## **WEATHERBOND PLUS**

	Algae/Fungus: Remove by high pressure wash or by chisel, scraper and treat with ANTI-		
	FUNGUS SOLUTION. Rinse again with clean water and dry.		
	Oil/Grease: Clean off with mild detergent and a little solvent if necessary. Wash thoroughly to remove all trace.		
Application Methods	Brush, roller or airless spray		
Paint Consumption	Theoretical: 9.0 - 12.0 m <sup>2</sup> / liter (30 – 40 µm DFT)		
Dilution	Not more than 10% of clean water if required		
	Roller & brush	- 10% maximum	
	Airless Spray	- 5% maximum	
Spray Application		Airless Spray	
	Delivery Pressure (kg/cm²)	120 - 150	
	Tip size at 60° angle	0.017"	
	Dilution	5% maximum	
Recommended	- 1 - 2 coats WEATHERBOND SKIMCOAT or NIPPON EXTERIOR PUTTY - 1 coat VINILEX 5100 WALL SEALER		
Painting System			
	- 2 coats WEATHERBOND PLUS		
Recommended Film Thickness per coat	30 – 40 microns DFT (Dry Film Thickness) per coat for standard application		
Drying Time	Surface dry: 30 minutes at 30°C		
Over coating Time	2 hours. Minimum based on normal conditions.		
Post Treatment	As the paint film is elastic, masking tapes used to protect surfaces not to be painted, e.g. door and window frames, should be removed with a knife or cutter.		
Cleaning	Wash all equipment immediately after use with clean water		
Storage	Keep containers tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.		
Packing	5 Liters & 15 Liters		
Precaution	Coverage depends on film thickness, roughness or porosity of the surface, loss during painting, etc.		
	The actual drying time and time before recoating may be shorter or longer, depending on film thickness, temperature, ambient humidity, ventilation, etc.		
		perature is below 10°C and the humidity is over 85%. Avoid kin. Use appropriate protective equipment.	
NOTE	The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product data sheet without further notice.		

Under license from NIPPON PAINT (SINGAPORE) Co., Pte Ltd. No.

1, First Lok Yang Road, Jurong, Singapore 629728, Singapore

