

NIPPON WEATHERBOND 8 YEARS

DESCRIPTION	A high-performance water-based paint that possesses superior exterior and interior durability
TYPE	Modified Acrylic Emulsion
USES	High grade emulsion with high grade decorative and protective functions for all internal and external masonry surfaces such: <ul style="list-style-type: none"> • brickwork • Plastered walls • cement • Texture masonry
FINISH	Low Sheen Color: Wide range of colors as per color card. Special colors on request.
FEATURES	<ul style="list-style-type: none"> • Excellent weathering under local climatic conditions Resistant to fungus and algae growth • Good adhesion on stable surfaces • Easy application with good levelling properties Excellent anti-carbonation properties • High water vapor permeability
APPLICATION DATA	
METHOD	Roller or brush
PAINT CONSUMPTION	Theoretical: 9.0 m ² /liter (Based on 40 microns DFT)
DILUTION	Ready for use, if necessary, dilution should not be more than 5 % water.
REQUIRED THICKNESS	40 to 50 microns (Dry Film Thickness per coat)
SURFACE PREPARATION	Ensure surface is clean, dry and stable. Remove loose surface matter and contaminants by appropriate means. Treat fungus growth areas with NIPPON ANTI-FUNGUSSOLUTION.
DRYING TIME	Touch dry : 30 minutes at 30°C Hard dry : 60 minutes at 30°C
OVERCOATING TIME	2 hrs. minimum.
CLEANING	Wash all equipment immediately after use with clean water.
STORAGE	Reseal lid and store remaining paint in a cool, clean and dry place. Contaminants can cause biodegradation of paint.
GENERAL INFORMATION	
SOLID CONTENT	Solid content: 57 ± 2.0 by Weight (based on white color)
SPECIFIC GRAVITY	1.45 ± 0.03 Kg/liter (based on white color)
PACKING	5 Liters & 18 Liters
SHELF LIFE	Up to 18 months in a tightly sealed container.
PRECAUTION	Ensure adequate protection and avoid direct contact on sensitive skin, eye, etc.
NOTE	The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product specification without further notice.