

VINILEX 5000 WALL SEALER

Nippon Vinilex 5000 low odour emulsion paint is a luxurious matt finish for interior walls. It enhances the sophisticated image of all modern homes and gives protection to walls from fungus and aglae.

Product Features:

- Low VOC
- Low Odour
- Easy application and touch-up
- Spatter resistance
- Excellent flow
- Non-toxic and lead, mercury and heavy metals free
- Fungus & mould resistant
- Environmentally friendly paint certified under the Singapore Green Building Product Certification Scheme

Paint Type	Product Type	Finishing	Recommended Substrate	Pack Size
Acrylic Polymer Emulsion	Interior	Matt	Plastered walls, Soft Boards, Gypsum, Primed timber, Primed metal, Brickwork & Fibre boards	5 Liters

APPLICATION DATA

METHOD	: Roller, brush or spray
THEORETICAL COVERAGE	: Approx 13 m ² / litre (30 microns DFT)
DILUTION	: No dilution is necessary for best performance

SURFACE PREPARATION

Ensure surface is clean, dry and stable using the following suggested surface treatments:

Moisture	: There must not be any water residue on the surface of the substrate. Moisture must be <4% (Sovereign moisture master) before application.
Unstable matter	: Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet wash or mechanical means such as power brush or scraper, whichever is suitable
Contaminants	: Remove dust and foreign matter by cleaning with damp cloth. Remove oil or grease using solvent or mild detergent. Allow surface to dry
Fungus and Algae	: Wash the affected area to remove unstable matters and micro-organisms. Apply Nippon Anti-Fungus Solution and leave on for at least 2 hours
Hairline cracks	: Fill cracks with suitable exterior grade waterresistant putty or filler

GENERAL INFORMATION

SOLID CONTENT	: 56.0 ± 2.0 % by weight (based on white colour)
SPECIFIC GRAVITY	: 1.39 ± 2.0 % kg / litre (based on white colour)
STORAGE	: Store in a tightly sealed container in a cool, dry place
SHELF LIFE	: Up to 24 months in a tightly sealed container

SAFETY PRECAUTION

- Keep container tightly closed and keep out of reach children or away from food and drink.
- Ensure good ventilation during application and drying.
- During application of paint, naked flames, welding operation, and smoking should not be allowed.
- When applying paint, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes from skin by using soap or water.
- Paint must always be stored in a cool place.
- When transporting paint, care must be taken. Always keep container in a secure upright position.
- Dispose-off any paint waste in accordance with the appropriate Environment Quality Regulations.

NOTE

The information given is intended to give a description of the product performance under specific test conditions. Nevertheless, we cannot assume any responsibility for the use of it since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.